

POE-W22W-4K 2800 Lumen PoE powered LED flood light

Product Features

- High brightness white-light
- IEEE802.3at compliant
- Under-voltage and Over-voltage Lockout
- Automatic or Manual operation
- Built-in Day/Night Sensor
- 2-Event PoE Classification Recognition
- 1 year warranty (requires POE surge arrester)



| PoE Flood Light | POE-W22W-4K |
|----------------------------------|---|
| Product Description | 2800 Lumen PoE powered LED flood light |
| Technical Specifications: | |
| Optical | |
| Typ. Brightness / flux (lm): | 2800 Lumen |
| Typ. Viewing angle: | 120 degrees |
| Typ. CCT: | 4000K |
| Typ. Efficacy (lm/W): | 252 |
| LEDs: | 2 |
| Interface | |
| Standard: | IEEE802.3at |
| Classification: | 2-Event Classification Recognition |
| Class: | 4 |
| Power consumption: | 23 Watt |
| Protection: | Under-voltage and Overvoltage Lockout Comprehensive Thermal Protection |
| Typ. operating voltage: | 48V |
| Maximum operating voltage: | 60V |
| Turn-On voltage: | 37.5V |
| Over-voltage lockout: | 70V |
| Under-voltage lockout: | 30V |
| Modes of operation | |
| Automatic: | Internal Day/Night sensor |
| Manual: | Aux. Contact |
| General | |
| Enclosure rating: | IP66 |
| Enclosure material: | Aluminium |
| Operating temperature: | -20°C to 75°C |
| Operating humidity: | 0% to 95%; non-condensing |
| Dimensions (mm): | 164 x 199 x 38 |